

<b>UTILITY PATENT APPLICATION TRANSMITTAL</b> <small>(Only for new nonprovisional applications under 37 CFR 1.53(b))</small>	Attorney Docket No.	113528	Total Pages	52
	First Named Inventor or Application Identifier			
	Vijay K. Bhagavath			
	Express Mail Label No.	EL363144738US		

<b>APPLICATION ELEMENTS</b> See MPEP chapter 600 concerning utility patent application contents.	<b>ADDRESS TO:</b> Assistant Commissioner for Patents Box Patent Application Washington, D.C. 20231
---	---

1. <input checked="" type="checkbox"/> <b>Fee Transmittal Form</b> <small>(submit an original, and a duplicate for fee processing)</small> 2. <input checked="" type="checkbox"/> <b>Specification</b> [Total Pages 21] <small>(preferred arrangement set forth below)</small> - Descriptive title of invention - Cross References to Related Applications - Statement Regarding Fed sponsored R&D - Reference to Microfiche Appendix - Background of the Invention - Brief Summary of the Invention - Brief Description of the Drawings(if filed) - Detailed Description - Claim(s) - Abstract of the Disclosure 3. <input checked="" type="checkbox"/> <b>Drawing(s)</b> (35 USC 113) [Total Sheets 18] 4. <b>Oath or Declaration</b> [Total Pages 5] a. <input checked="" type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application(37 CFR 1.63(d)) <small>(for continuation/divisional with Box 17 completed)</small> <small>[Note Box 5 below]</small> i. <input type="checkbox"/> <b>DELETION OF INVENTOR(S)</b> <small>Signed statement attached deleting inventor(s)          named in the prior application, see 37 CFR          163(d)(2) and 1.33(b)</small> 5. <input type="checkbox"/> <b>Incorporation by reference</b> (useable if Box 4b is checked) <small>The entire disclosure of the prior application, from which a copy of the oath          or declaration is supplied under Box 4b, is considered as being part of the          disclosure of the accompanying application and is hereby incorporated by          reference herein.</small>	6. <input type="checkbox"/> Microfiche Computer Program (Appendix) 7. <input type="checkbox"/> Nucleotide and/or Amino Acid Sequence Submission <small>(if applicable, all necessary)</small> a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy(identical to computer copy) c. <input type="checkbox"/> Statement verifying identity of above copies  <div style="text-align: center;"><b>ACCOMPANYING APPLICATION PARTS</b></div> 8. <input checked="" type="checkbox"/> Assignment Papers(cover sheet & document(s)) 9. <input type="checkbox"/> 37 CFR 3.73(b)Statement <input type="checkbox"/> Power of Attorney 10. <input type="checkbox"/> English Translation Document (if applicable) 11. <input type="checkbox"/> Information Disclosure <input type="checkbox"/> Copies of IDS <small>Statement(IDS)/PTO-1449 Citations</small> 12. <input type="checkbox"/> Preliminary Amendment 13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) <small>(Should be specifically itemized)</small> 14. <input type="checkbox"/> Small Entity <input type="checkbox"/> Statement filed in prior application, <small>Statement(s) Status still proper and desired</small> 15. <input type="checkbox"/> Certified Copy of Priority Document(s) <small>(if foreign priority is claimed)</small> 16. <input type="checkbox"/> Other :
--	---

17. If a **CONTINUING APPLICATION**, check appropriate box and supply the requisite information:  
☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior Application No:

**18. CORRESPONDENCE ADDRESS**

<input type="checkbox"/> Customer Number or Bar Code Label	(Insert Customer No. or Attach bar code label here)	or <input checked="" type="checkbox"/> Correspondence address below
--	---	---

NAME	Samuel H. Dworesky				
ADDRESS	AT&T CORP., P.O.BOX 4110				
CITY	MIDDLETOWN	STATE	NEW JERSEY	ZIP CODE	07748-4801
COUNTRY	UNITED STATES			FAX	732-957-5505

**19. SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED**

NAME	Thomas A. Restaino		Reg. #	33444
TELEPHONE	908-903-6466			
SIGNATURE	<i>Thomas A. Restaino</i>		DATE	July 13, 1999

"Express Mail" Mailing Label Number EL363144738US Date of Deposit 7/13/99  
 I hereby certify that this Application  
 Is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and  
 is addressed to the Assistant Commissioner of Patents, Washington D.C., 20231

ANN E. TAYLOR  
(Printed Name of Person Mailing Paper)  
*Ann E. Taylor*  
(Signature of Person Mailing Paper)

## **A Network-Based Service For Recipient-Initiated Automatic Repair Of IP Multicast Sessions**

Inventors: Vijay K. Bhagavath, Joseph T. O'Neil, David Shur, and Aleksandr Zelezniak

5

### **Related Patent Applications**

This patent application is related to the copending US Patent Application Serial Number 09/271,116, filed March 17, 1999, entitled "A Network-Based Service for the  
10 Repair of IP Multicast Sessions", by Nicholas Maxemchuk, David McManamon, David Shur, and Aleksandr Zelezniak, assigned to AT&T Corp. and incorporated herein by reference.

This patent application is also related to the copending US Patent Application Serial Number 09/306,089 filed May 6, 1999, entitled "A Network-Based Service for  
15 Originator-Initiated Automatic Repair of IP Multicast Sessions", by Vijay K. Bhagavath, Joseph T. O'Neil, David Shur, and Aleksandr Zelezniak, assigned to AT&T Corp. and incorporated herein by reference.

### **Background Of The Invention**

20

IP multicasting provides an efficient way for a source to send a stream of User Datagram Protocol (UDP) packets to a set of recipients. The source sends only one copy of each packet to an IP network, such as the Internet, for example. The routers in the IP network do the work required to deliver that packet to each recipient. Various IP  
25 multicast routing protocols can be used in an IP network. These allow the routers to communicate with each other so that the multicast datagrams are sent only to those subnetworks with receivers that have joined a multicast session.

A multicast session is identified by an IP address and port number. The IP address is a Class D address in the range from 224.0.0.1 to 239.255.255.255. IP  
30 multicasting is more efficient than unicasting for group communication. Unicasting requires that the source send a separate copy of each datagram to each recipient. This requires extra resources at the source and in the IP network and is wasteful of network bandwidth.

Some useful background references describing IP multicasting in greater detail  
35 include: (1) Kosiur, D., IP Multicasting: The Complete Guide to Corporate Networks, Wiley, 1998; (2) Maufer, T., Deploying IP Multicast in the Enterprise, Prentice-Hall,

1997; (3) Deering, S., "Host Extensions for IP Multicasting," Network Working Group Request for Comments Internet RFC-1112, August 1989; (4) Waitzman, D., Partridge, C., Deering, S., "Distance Vector Multicasting Routing Protocol," Network Working Group Request for Comments Internet RFC-1075, November 1988; (5) Schulzrinne, H., Casner, S., Frederick, R., Jacobson, V., "RTP: A Transport Protocol for Real-Time Applications," Network Working Group Request for Comments Internet RFC 1889, July 18, 1994. The IP multicast protocol set forth in the IETF RFC 1112 "Host Extensions for IP Multicasting" is the standard protocol for enabling hosts to establish and conduct IP multicast sessions on the Internet. The IETF RFC 1075, "Distance Vector Multicast Routing Protocol (DVMRP)," describes a protocol for propagating routing information among multicast-enabled routers.

The multicast backbone on the Internet (Mbone) is an extension of the Internet backbone to support IP multicasting. The Mbone is formed collectively by the portion of the network routers in the Internet backbone that are programmed to perform the IP multicast routing protocol. Those routers in the Internet backbone that are programmed to handle IP multicast sessions, as well as unicast sessions, are referred to herein as multicast-enabled routers. The Mbone is a virtual network that is layered on top of sections of the physical Internet. It is composed of islands of multicast-enabled routers connected to each other by virtual point-to-point links called "tunnels." The tunnels allow multicast traffic to pass through the non-multicast-enabled routers of the Internet. IP multicast packets are encapsulated as IP-over-IP, so that they look like normal unicast packets to the intervening routers. The encapsulation is added upon entry to a tunnel and removed upon exit from a tunnel. This set of multicast-enabled routers, their directly connected subnetworks, and the interconnecting tunnels define the Mbone. For additional details, see (1) Comer, Douglas E. Internetworking with TCP/IP: Volume 1- Principles, Protocols, and Architecture, Third Edition. Englewood Cliffs, NJ: Prentice Hall, 1995; (2) Finlayson, Ross, "The UDP Multicast Tunneling Protocol", IETF Network Working Group Internet-Draft, published September 9, 1998, <http://search.ietf.org/internet-drafts/draft-finlayson-umtp-03.txt>; and (3) Eriksson, Hans, "MBone: The Multicast Backbone," Communications of the ACM, August 1994, Vol.37, pp.54-60.

Since the multicast-enabled routers of the Mbone and the non-multicast-enabled routers of the Internet backbone have different topologies, multicast-enabled routers execute a separate routing protocol to decide how to forward multicast packets. The majority of the Mbone routers use the Distance Vector Multicast Routing Protocol (DVMRP), although some portions of the Mbone execute either Multicast OSPF

(MOSPF) or the Protocol-Independent Multicast (PIM) routing protocols. For more details about PIM, see: Deering, S., Estrin, D., Farrinaci, D., Jacobson, V., Liu, C., Wei, L., "Protocol Independent Multicasting (PIM): Protocol Specification", IETF Network Working Group Internet Draft, January, 1995.

5           Multicasting on the Internet has a unique loss environment. On a particular path the losses occur in bursts, as multicast-enabled routers become congested, rather than the losses having the characteristics associated with white noise. When packets are lost on a particular link in the multicast tree, any downstream receivers lose the same packet. Therefore, a large number of retransmissions may occur at the same time in response to  
10   negative acknowledgments from receivers. One problem is that such retransmissions are typically in multicast sessions which will tend to encounter the same congested nodes as did the original multicast sessions.

          However, congestion in different parts of network is not correlated since traffic to receivers in other parts of the multicast tree does not necessarily pass through the same  
15   congested nodes and therefore does not lose the same bursts of packets. Therefore, path diversity would be a good means for recovering at least some of the missing packets, if there were a way to coordinate such a recovery.

          Another problem in IP multicasting is that some Internet Service Providers (ISPs) discriminate against multicast packets and discard them before discarding the packets for  
20   other services. Therefore, it would be worthwhile balancing the efficiency of multicast transmissions with the quality of point-to-point transmissions.

          These problems have been solved by the Network-Based Service for the Repair of IP Multicast Sessions described in the above referenced, copending US patent application by Maxemchuk, et al. In the Maxemchuk, et al. system, a repair server polls multiple  
25   transmit servers to accumulate as many of the packets missing from the multicast session as possible. This improves the quality of audio and video multicasts of live conferences, news broadcasts and similar material from one source to many receivers over the Internet.

          The invention disclosed herein is an improvement to the Maxemchuk, et al. system, to provide authentic, paying subscribers an automatic repair service for the  
30   multicast sessions they receive. The invention disclosed herein also provides for the receiving subscriber to be authorized by a subscription server that causes the subscriber to be billed for the repair service.

## Summary of the Invention

The invention is a system and method for recipient-initiated automatic repair of IP multicast sessions. In one aspect of the invention, a multicast application on a receiver  
5 issues a request to join an IP multicast session "X". A translator/decryption module (TDM) on the receiver intercepts this request and sends it to a controller on a repair server. The controller sends a request to a subscription server to determine if this user has subscribed to the repair service. The controller upon receipt of a positive response  
10 from the subscription server, then determines whether a repair/encryption module (REM) exists for this multicast session. If it does not receive such a response, then the controller selects an IP multicast address, port number and decryption key for a new IP multicast session "Y". This information is returned to the TDM. The controller creates a repair/encryption module (REM) and provides the IP multicast address and port number  
15 for the new IP multicast session "Y" and an encryption key to the REM. Then, the TDM stores the session "Y" IP multicast address, port number and decryption key.

The REM reads packets from IP multicast session "X" and checks if there are any missing packets. If there are missing packets, it requests one or more retransmit servers  
20 for session "X" to obtain the missing packets. The repair/encryption module encrypts the packets and writes them to IP multicast session "Y". The packets for IP multicast session "Y" are processed by the IP stack on the receiver, and are then sent to the translator/decryption module (TDM). The TDM decrypts these packets, modifies the destination IP address and port number from the values for session "Y" to those for session "X". The packets are then sent to the application. The application then presents  
25 the message contained in the packets to the subscriber of the IP multicast "X".

## Description of the Figures

Figure 1 is an overall network diagram showing the relationship of multicast sources, a plurality of retransmit servers, repair servers, and receivers in the Internet  
30 network.

Figure 1A shows a functional block diagram of the repair server repairing a multicast session "X" which has undergone some packet losses after transmission from the multicast source, into a repaired multicast session "Y" which is forwarded by the router to the receiver.

35 Figure 1B shows a functional block diagram of the repair server repairing two multicast sessions "X1" and "X2" which have each undergone some packet losses.

Figure 1C shows the graphical user interface running on the subscriber's receiver, where the recipient subscriber can initiate a request to join an IP multicast session "X2". The translator/decryption module (TDM) on the receiver intercepts this request and sends it to the controller on the repair server. The controller sends a request to the subscription server to determine if this user has subscribed to the repair service.

Figure 1D shows the controller receiving a positive response from the subscription server. The controller selects an IP multicast address, port number and decryption key for a new IP multicast session "Y2", which is returned to the TDM.

Figure 1E is an alternate embodiment of the network of Figure 1, showing an alternate, bypass network used for the responses from the retransmit servers to the repair server, of the portions of missing packets.

Figure 2A illustrates the packets currently being output by the multicast source.

Figure 2B illustrates the packets currently being delivered to the repair server.

Figure 2C illustrates the packets currently being delivered to the recipients by the repair server.

Figure 2D illustrates the RTCP source description packet periodically output by the multicast source.

Figure 2E illustrates the RTCP sender report packet periodically output by the multicast source.

Figure 2F illustrates the packets in the repaired multicast session 111' constructed by the repair server, which appear to the recipient receivers to be the same Group\_1 session transmitted from source, having the same multicast IP address and port number as that for the original packet stream of Figure 2A.

Figure 2G illustrates, in the alternative, that the repaired multicast session 111'' can be a different session that is selectively chosen as a repaired multicast session by the recipient receivers, having a different multicast IP address and port number than that for the original packet stream of Figure 2A.

Figure 2H unicast request 150A from the repair server 120A to the retransmit server 110A for missing packets.

Figure 2I unicast response 160A to repair server with detected ones of specified packets in buffer.

Figure 3A and 3B show a flow diagram 1100 for the recipient-initiated automatic repair of IP multicast sessions.

Figure 4A is a data flow diagram showing the flow of data through the repair server 120A.

Figure 4B is a detailed functional block diagram of the repair server 120A.

## Discussion of the Preferred Embodiment

Figure 1 is an overall network diagram showing a multicast source 102 that is transmitting a Group\_1 multicast session 100, whose packets 103 are currently being output by the multicast source 102. The packets pass through the multicast enabled router 104 and are output on line 128 to the Internet backbone 106. A second multicast source 102' is shown transmitting a second Group\_2 multicast session onto the Internet backbone 106.

A plurality of retransmit servers 110A, 110B, 110C, and 110D are also shown connected to the Internet backbone 106. Each retransmit server, for example 110A, includes a circular buffer that stores a running segment of the multicast Group\_1 session received from the source 102, for example the most recent three second interval of the received session. The session packet stream 103 sent from the source 102 may undergo some packet losses by the time it reaches the retransmit server 110A. Each retransmit server, for example 110A, includes a buffered packet detector that can identify the packets that have been received from the Group\_1 session. It can also take advantage of the Real-Time Control Protocol (RTCP), to estimate the number of packets that have been missed from the session. Each retransmit server, for example 110A, includes a message processor that handles message formation and transmission and which handles message receipt and interpretation for message exchanges with other nodes on the network. Refer to the above referenced copending patent applications by Nicholas Maxemchuk, et al. and by Vijay K. Bhagavath, et al, incorporated herein by reference, for a description of the retransmit server features.

The multicast source 102 uses the Real-Time Transport Protocol (RTP) to multicast the packets 103. The Real-Time Transport Protocol (RTP) is carried over User Datagram Protocol (UDP) packets over IP networks from the source 102 to the repair server 120A, and from the source 102 to the retransmit servers 110A, 110B, 110C, and 110D. RTP provides timestamps and sequence numbers. Both the retransmit servers 110A, 110B, 110C, and 110D and the repair server 120A and 120B can use this information to identify when some of the packets 103 are lost or arrive out of sequence. RTP also supports payload type identification, synchronization, encryption and multiplexing and demultiplexing on a per-user basis. For more detailed information on RTP, see (1) Schulzrinne, H., Casner, S., Frederick, R., Jacobson, V., "RTP: A Transport Protocol for Real-Time Applications", Network Working Group Request for

Comments Internet RFC 1889, January 1996; (2) Kosiur, D. IP Multicasting: The Complete Guide to Corporate Networks, Wiley, 1998.

In Figure 1, the Internet backbone is shown including a first path that includes multicast-enabled routers 105, respectively labeled 1A, 1B, 1C, and 1D, forming the Mbone portion that can handle IP multicast sessions, such as Group\_1 session 100. The Internet backbone is also shown including a second path that includes non-multicast-enabled routers 107, respectively labeled 1E and 1F, which cannot handle IP multicast sessions. Because heavy multicast traffic levels occur that can only be handled by the multicast-enabled routers 105, these routers tend to see high levels of congestion more often than do the non-multicast-enabled routers 107. Repair servers 120A and 120B are shown in Figure 1 connected to the Internet backbone 106.

Figure 1 also shows a second plurality of receivers 124B, 124B', and 124B'' are shown connected through the multicast-enabled router 122B to the repair server 120B. Receivers 124B and 124B' are receiving the Group\_1 session and receiver 124B'' is receiving the Group\_2 session. Figure 1 also shows a subscription server 170 and its database 174 connected to the Internet backbone 106. The subscription server 170 is connected through interface 171 to the billing system 172.

Figure 1A shows a functional block diagram of the repair server 120A repairing a multicast session "X" which has undergone some packet losses after transmission from the multicast source 102, into a repaired multicast session "Y" which is forwarded by the router 122A to the receiver 124A. Figure 1B shows a functional block diagram of the repair server 120A repairing two multicast sessions "X1" and "X2" which have each undergone some packet losses. Figures 1C and 1D are functional block diagrams showing an example sequence in the operation of the invention to enable recipient initiated multicast repair of a multicast session "X2" that has undergone some packet losses after transmission from the multicast source 102, converting into a repaired multicast session "Y2" which is forwarded by the router 122A to the receiver 124A. Figures 1C and 1D can be viewed with the flow diagram of Figures 3A and 3B.

Figure 1C shows the graphical user interface 1402 running on the subscriber's receiver 124A. The recipient subscriber can initiate a multicast application 1220 on receiver 124A by issuing a request to join an IP multicast session "X2", as shown in step 1102 of Figure 3A.

Figure 1C shows the translator/decryption module (TDM) 1222 on the receiver intercepting this request and sending it to the controller 456 on the repair server 120A, as shown in step 1104 of Figure 3A. The TDM on the receiver intercepts an application request to repair a specific IP multicast session. This request is sent from the application



to the TDM. An application programming interface (API) is provided by the TDM. This API enables a multicast session to request that a specific IP multicast session be repaired.

Figure 1C shows the controller sending a request to the subscription server 170 of Figure 1 to determine if this user has subscribed to the repair service, as shown in step 1106 of Figure 3A. The subscription server's database 174 contains the identity of the individuals who are allowed to use this service. In addition, it contains a variety of other data about that individual. For example, credit card information is stored so that the individual can be charged for these repaired sessions. The subscription server 170 has an interface 171 with the billing system 172 of Figure 1, so that it can send charges to the billing system. It is then the responsibility of the billing system to issue the appropriate bills 175 to the recipient on a periodic basis.

Figure 1D shows the controller 456 receiving a response from the subscription server 170. If it is a negative response, then this user has not subscribed to the repair service and the request is not honored by the controller. If it is a positive response from the subscription server, as shown in step 1108 of Figure 3A, then step 1109 of Figure 3A determines if a repair/encryption module (REM) 454 exists for this multicast session. If it does, then the process flows to step 1113 of Figure 3B. If it does not, then the process flows to step 1110 of Figure 3A. The controller 456 has a simple data structure to track which REMs are repairing which multicast sessions. A plurality of REMs can be in existence simultaneously, one for each multicast session to be repaired. When a multicast session ends, the corresponding REM is deleted. This relinquishes the memory and processor resources in the repair server 120A that a REM is using.

Figure 1D shows the controller selecting an IP multicast address, port number and decryption key for a new IP multicast session "Y2". This information is returned to the TDM 1222, as shown in step 1110 of Figure 3A. In step 1112 of Figure 3A, the controller creates a repair/encryption module (REM) 454 and provides the IP multicast address and port number for the new IP multicast session "Y2" and encryption key to the REM 454'. In step 1113 of Figure 3B, the TDM 1222 stores the session "Y2" IP multicast address, port number and decryption key. The range of valid IP multicast address is 224.0.0.0 to 239.255.255.255. (Some of the addresses in this range are reserved for special purposes.) The repair server 120A can easily determine which IP multicast address/port pairs are currently in use by examining the destination address and port of the packets that go through it. This is the same machine on which the REM(s) execute. This enables the controller 456 on the repair server to select an IP multicast address/port pair that is not currently used. When the controller 456 selects an unused IP multicast address/port combination, it can easily check the table in which it records the IP multicast

address/port combination for each REM. If a REM already exists to repair that IP multicast session, that REM can be used. If a REM does not already exist to repair that IP multicast session, a new REM is created. In the repair server, there is one entry in the REM table for each REM. That entry records: (a) the IP address/port of the session to be repaired, (b) the IP address/port of the repaired and encrypted version of that session, and (c) the encryption key. Each REM 454 can be implemented as an object-oriented object. The instance variables of that object are: (a) the IP address/port of the session to be repaired, (b) the IP address/port of the repaired and encrypted version of that session, and (c) the encryption key. The REM object has methods that implement its various functions. The implementation programming language can be C, C++, Java, or other object-oriented programming language.

Then in step 1114 of Figure 3B, the REM reads packets from IP multicast session "X2" and checks if there are any missing packets. If so, it requests one or more retransmit servers for session "X2" to obtain missing packets. In step 1116 of Figure 3B, the repair/encryption module 454 encrypts the packets and writes them to IP multicast session "Y2". Each IP packet contains a header and data. Only the data is encrypted by the REM. The header contains the destination IP address and thus it can not be encrypted. A standard encryption algorithm can be used, such as DES or IPSEC.

In step 1118 of Figure 3B, the packets for IP multicast session "Y2" are processed by the IP stack 1224 on receiver 124A. The IP stack contains the Transport, Network, Data Link, and Physical layers and performs the standard processing for IP packets. The processed packets are then sent to the translator/decryption module (TDM) 1222. In step 1120 of Figure 3B, the TDM 1222 decrypts these packets, modifies the destination IP address and port number from the values for session "Y2" to those for session "X2". The packets are sent to application 1220. Then in step 1122 of Figure 3B, the application presents the packets to the subscriber for IP multicast "X2". The application 1220 needs to be cognizant of the address information. A multicast application 1220 that receives packets can display the IP multicast address/port combination on which it is receiving. For example, an application that presents streaming audio and video from the Internet can display this information. This information can be thought of as analogous to "channel numbers" in radio or TV. Similarly, a videoconferencing application that works with a camera to capture an image, needs to transmit the packets that it generates. The videoconferencing application must know which IP address/port combination is to receive this data.

The packets 103 being transmitted by the multicast source 102 in Figure 1, are shown in Figure 2A. Figure 2A illustrates the packets 103 currently being output by the

multicast source 102, with packets 281 to 290 being shown. Figure 2B illustrates the packets 109 currently being delivered to the repair server 120A, namely packets 281, 282, 289, and 290. Note that packets 283 - 288 are missing from the received session. A plurality of receivers 124A, 124A', and 124A'' are shown connected through the

5 multicast-enabled router 122A to the repair server 120A. Receivers 124A and 124A'' are receiving the Group\_1 session. Figure 2C illustrates the packets 111 currently being delivered to the recipients at receivers 124A and 124A'' by the repair server 120A, namely packets 205 - 214 which are being buffered for a three-second delay in the repair server 120A, before being multicast to receivers 124A and 124A''. Receiver 124A' is

10 shown receiving the second multicast Group\_2 session from repair server 120A. Figure 2D illustrates the RTCP source description packet 103' is periodically output by the multicast source 102. Figure 2E illustrates the RTCP sender report packet 103'' periodically output by the multicast source 102. The Real-Time Control Protocol (RTCP) is the control protocol that is used in conjunction with RTP. Senders 102 can

15 report the number of packets and bytes that are sent. Receivers can report on the loss, delay, and observed jitter (per sender). Other functions include media synchronization, network time protocol (NTP) and RTP timestamp correlation, and session control. For more details on RTCP, see (1) Kosiur, D., IP Multicasting: The Complete Guide to Corporate Networks, Wiley, 1998; and (2) Thomas, S., Ipng and the TCP/IP Protocols: Implementing the Next Generation Internet, Wiley, 1996.

The RTCP source description packet 103' of Figure 2D periodically describes in the TOOL field the media tool or application in the source 102 that is generating the packets 103, such as an MPEG2 video and audio compression program. The RTCP source description packet 103' can also describe in the NOTE field the current state of the

25 source, such as the current number of audio channels included in the MPEG2 transmission.

The RTCP sender report packet 103'' in Figure 2E periodically reports the sender's packet count for the source 102. This is the total number of RTP data packets transmitted by the source 102 since starting transmission up until the time this packet

30 103'' was generated. The RTCP sender report packet 103'' in Figure 2E also periodically reports the sender's octet count for the source 102. This is the total number of payload octets (i.e., not including header or padding) transmitted in RTP data packets by the source 102 since starting transmission up until the time this packet 103'' was generated. This field can be used to estimate the average payload data rate.

35 The retransmit servers periodically transmit RTCP receiver reports on the quality of the multicast Group\_1 session as received from the source 102. The format of the

receiver report (RR) packet is substantially the same as that of the sender report (SR) packet except for minor differences, and except that the packet type field indicates that it is a receiver report. The remaining fields have the same meaning as for the SR packet. The RTCP receiver report includes the SSRC\_n (source identifier) field that identifies the source 102 to which the information in this reception report pertains. The RTCP receiver report includes the fraction lost field which provides the fraction of RTP data packets from source SSRC\_n lost since the previous SR or RR packet was sent. This fraction is defined to be the number of packets lost divided by the number of packets expected, as defined below. The RTCP receiver report includes the cumulative number of packets lost 10 field, which provides the total number of RTP data packets from source SSRC\_n that have been lost since the beginning of reception. This number is defined to be the number of packets expected less the number of packets actually received, where the number of packets received includes any which are late or duplicates. Thus packets that arrive late are not counted as lost, and the loss may be negative if there are duplicates. The number of packets expected is defined to be the extended last sequence number received, as 15 defined next, less the initial sequence number received. The RTCP receiver report includes the extended highest sequence number received field, which provides the highest sequence number received in an RTP data packet from source SSRC\_n. The RTCP receiver report includes the interarrival jitter field which provides an estimate of the statistical variance of the RTP data packet interarrival time, measured in timestamp units and expressed as an unsigned integer. The interarrival jitter J is defined to be the mean deviation (smoothed absolute value) of the difference D in packet spacing at the receiver compared to the sender for a pair of packets. This is equivalent to the difference in the "relative transit time" for the two packets; the relative transit time is the difference 25 between a packet's RTP timestamp and the receiver's clock at the time of arrival, measured in the same units. The interarrival jitter is calculated continuously as each data packet "i" is received from source SSRC\_n, using this difference D for that packet and the previous packet i-1 in order of arrival (not necessarily in sequence). Whenever a reception report is issued, the current value of J is sampled. The RTCP receiver report includes the last SR timestamp (LSR) field that provides the NTP timestamp received as part of the most recent RTCP sender report (SR) packet from source SSRC\_n. The RTCP receiver report includes the delay since last SR (DLSR) field, which provides the delay, between receiving the last SR packet from source SSRC\_n and sending this reception report. Let SSRC\_r denote the receiver issuing this receiver report. Source SSRC\_n can 35 compute the round-trip propagation delay to SSRC\_r by recording the time A when this reception report is received. It calculates the total round-trip time A-LSR using the last

SR timestamp (LSR) field, and then subtracting this field to leave the round-trip propagation delay as  $(A - LSR - DLSR)$ . This information can be transferred from the source 102 to the retransmit server 110A in the RTCP sender report or the RTCP source description. This field in the RTCP receiver report from the retransmit server 110A may be used as an approximate measure of distance between the source 102 and the retransmit server 110A, although some links have very asymmetric delays. For more details on RTCP, see Schulzrinne, H., Casner, S., Frederick, R., Jacobson, V., "RTP: A Transport Protocol for Real-Time Applications," Network Working Group Request for Comments Internet RFC 1889, July 18, 1994.

Each repair server, for example 120A in the data flow diagram of Figure 4A, includes a delay buffer 140A that stores a running segment of the multicast Group\_1 session received from the source 102, for example the most recent three-second interval of the received session. This three-second delay is applied to the arriving packets 109 before they are forwarded in multicast mode to the receivers 124A and 124A". The session packet stream 103 sent from the source 102 may undergo some packet losses by the time it reaches the repair server 120A. Figure 2B shows the packets 109 from the Group\_1 session received by the repair server 120A, namely packets 281, 282, 289, and 290. Note that packets 283 - 288 are missing. Each repair server, for example 120A in Figure 2, includes a missing packet detector 144A that can identify the packets that have been lost from the Group\_1 session. The retransmit server list 146A is compiled by a server list updating program 444. The list 146A is an ordered list of the retransmit servers 110A - 110D. This list 146A is compiled to enable the repair server 120A to identify which of the several retransmit servers 110A - 110D is the most likely one to have the best copy of the Group\_1 session packets, in the event that they are needed for repair. The server list updating program 444 can also take advantage of the Real-Time Control Protocol (RTCP) to estimate the number of packets that each retransmit server 110A - 110D has missed from the session. The server list updating program 444 can apply a number of performance criteria to rank the respective retransmit servers 110A - 110D in the server list 146A. Each repair server, for example 120A in Figure 4A, includes a message processor 142A that handles message formation and transmission and which handles message receipt and interpretation for message exchanges with other nodes on the network. Figure 4B is a detailed functional block diagram of a repair server 120A. Refer to the above referenced copending patent applications by Nicholas Maxemchuk, et al. and by Vijay K. Bhagavath, et al, incorporated herein by reference, for a description of additional repair server features.

The ranking criteria that the server list updating program 444 in the repair server 120A can apply to rank the respective retransmit servers 110A - 110D in a server list 146A can be based on the RTCP receiver reports multicast by each of the retransmit servers 110A - 110D. The RTCP receiver report includes the fraction lost field which provides the fraction of RTP data packets from source SSRC\_n lost by a retransmit server 110A, for example, since the previous SR or RR packet was sent. The RTCP receiver report includes the cumulative number of packets lost field, which provides the total number of RTP data packets from source SSRC\_n that have been lost by a retransmit server 110A, for example, since the beginning of reception. The RTCP receiver report includes the interarrival jitter field which provides an estimate of the statistical variance of the RTP data packet interarrival time experienced by a retransmit server 110A, for example, measured in timestamp units and expressed as an unsigned integer. The round propagation delay between the source and a retransmit server 110A, for example, may be used as an approximate measure of distance between the source 102 and the retransmit server 110A.

The repair server 120A, for example, maintains the ordered list 146A of the retransmission servers 110A - 110D shown in Figure 1, that are most likely to have buffered copies of packets missing from the Group\_1 session. When the repair server 120A detects that there are packets missing from the session it has received, it uses the ordered list 146A to sequentially request the missing packets from respective ones of the plurality of retransmission servers 110A - 110D. Assume for this example that the list 146A places the retransmit servers in the order from highest to lowest as 110A, 110B, 110C, 110D, based on the total packets lost, as reported by the RTCP receive report which is multicast by each respective retransmit server 110A - 110D. Since retransmit server 110A has reported that it has the fewest total packets lost (4 packets), it is ranked as the most probable to have buffered copies of the missing packets. Figure 2H shows the first unicast request 150A from the repair server 120A to the retransmit server 110A for missing packets. Figure 2I illustrates the packets 500A in the unicast response of the first portion of missing packets on hand at the first retransmit server 110A, namely packets 283 and 284. The recovered packets 283 and 284 are added by the repair server 120A to the delay buffer 140A. If the missing packet detector 144A detects that additional packets remain missing, then additional retransmit servers 110B, etc. are requested by the repair server 120A to return additional missing packets.

Each IP multicast source 102 periodically transmits Session Description Protocol (SDP) announcements to inform potential receivers 124A about the existence of a session. In order to join an IP multicast session, software at the receiver 124A, for

example, must know the IP address and port of that session. One way this can be done is for the source 102 to periodically announce this information on a well-known IP multicast session. The Session Description Protocol (SDP) used serves two primary purposes: (a) to communicate the existence of a session and (b) to convey sufficient information so end users may join the session. Some of the information included in an SDP datagram is: the name and purpose of the session, time(s) the session is active, the media comprising the session, the transport protocol, the format, and the multicast address and port. Software developers may add other attributes to SDP announcements for specific applications. For more detailed information on SDP, see Handley, M. and Jacobson, V., "SDP: Session Description Protocol", Network Working Group Request for Comments Internet RFC 2327, Nov. 1997.

Repaired packets are transmitted from the retransmit servers 110A - 110D in a unicast session. Then, the repair server 120A forwards the repaired session as a multicast session 111' to the receivers 124A and 124A''. The repaired multicast session 111' is constructed by the repair server 120A by combining the packets 109 of Figure 2B received in the delay buffer 140A with the missing packets received from the retransmit servers 110A - 110D. Figure 2I illustrates the packets 500A in the unicast response of the first portion of missing packets on hand at the first retransmit server 110A, namely packets 283 and 284.

The repaired multicast session 111' constructed by the repair server 120A resumes using the RTP format as shown in Figure 2F. Figure 2F illustrates the packets 111' that are sequentially ordered in the delay buffer in time to be transmitted in a multicast session to the recipient receivers 124A and 124A''. For example, missing packets 283 and 284 from the first retransmit server 110A are placed in order following packet 282 in the delay buffer 140A. The delay buffer 140A can be organized for indirect addressing of packets that are buffered at various locations in the buffer 140A. The pointers are sequentially addressed to provide the desired order for the output stream of packets 111'. Each pointer respectively points to a location in the delay buffer 140A where a packet having a sequence number is stored. A first pointer in the output sequence points to packet 282. The next pointer in the output sequence is made to point to the recovered packet 283. The next pointer thereafter in the output sequence is made to point to the recovered packet 284. In this manner, when missing packets are recovered from the retransmit servers, they can be stored at any available location in the delay buffer 140A and the pointer for that packet sequence number is made to point to the storage location of the recovered packet.

The packets in the multicast session 111' of Figure 2F constructed by the repair server 120A resume using the RTP format. The multicast session 111' can appear to the recipient receivers 124A and 124A'' to be the same Group\_1 session transmitted from source 102, as is shown in Figure 2F, having the same multicast IP address and port number as that for the original packet stream 103 of Figure 2A.

In the alternative, the multicast session 111'' can be a different session that is selectively chosen as a repaired multicast session by the by recipient receivers 124A or 124A'', as is shown in Figure 2G, having a different multicast IP address and port number than that for the original packet stream 103 of Figure 2A. The recipients' subnetwork router 122A can make both the unrepaired multicast session 109 from path 155 and the repaired multicast session 111'' from repair server 120A available to the recipient receivers 124A and 124A''. The second, repaired multicast session 111'' can be selectively subscribed to by the recipients if they find that the unrepaired session 109 has insufficient quality for their purposes.

Figure 4B is a detailed functional block diagram of a repair server. Memory 402 is connected by bus 404 to the CPU processor 406 that executes the instructions in programs stored in memory 402. Bus 404 also connects to hard drive storage 408, network interface card 410 which connects to the Internet backbone 106, and network interface card 412 which connects to the alternate, bypass network 600 of Figure 1I. Memory 402 has stored in it the delay buffer 140A, missing packet detector program 144A, repair module 455, controller 456, repair/encryption module 454, repair/encryption module 454', retransmit server list 146A, server list updating program 444, message processor program 142A, retransmit server monitor program 452, internet group management protocol 432, user datagram protocol 434, internet control message protocol 436, transmission control protocol 438, repair server logic program 440, operating system 442, IP multicast routing daemon 445, real-time control protocol 446, session description protocol 448, and real-time transport protocol 450. The IP Multicast Routing Daemon 445, as shown in Figure 4B, is optional and communicates with multicast routing daemons on other routers to determine when the datagrams for a multicast session should be routed from one interface to another interface. The functionality of a multicast firewall can also be included. The communication from the repair server 120A to a retransmit server 110A in making a request for session repair may be multicast, instead of unicast, if the Mbone portion of the Internet backbone is not too congested.

Figure 1E is an alternate embodiment of the network of Figure 1, showing an alternate, bypass network 600 used for the responses from the retransmit servers 110A, etc. to the repair server 120A, of the portions of missing packets. In accordance with the



invention, in response to the requests, a message processor in at least one of the retransmit servers 110A, retransmits in a bypass session to the repair server 120A, at least a portion the missing packets. The retransmitted packets in the bypass session are forwarded to circumvent at least some of the congested, multicast enabled routers 105 in the Internet backbone 106. This can be accomplished by transmitting the missing packets over a separate dial-up network 600 or a private virtual network 600 from the retransmit servers 110A, etc. to the repair server 120A. Another way this can be accomplished is by transmitting the missing packets in a unicast session from the retransmit servers 110A, etc. to the repair server 120A. The unicast response enables non-multicast enabled routers 107 in the Internet backbone to handle the response, thereby circumventing at least some of the congested multicast-enabled routers 105.

Various illustrative examples of the invention have been described in detail. In addition, however, many modifications and changes can be made to these examples without departing from the nature and spirit of the invention.

What is claimed is:

1. A network for communicating multicast packets in a multicast session from a source to a plurality of multicast recipients in that session, comprising:

5 a repair server in the network monitoring received ones of the packets to said recipients, the repair server including a missing packet detector; and

at least one retransmit server in the network buffering portions of the packets during the session;

10 said repair server detecting missing packets and in response to a subscriber request for repair services, requesting missing packets from said retransmit server.

2. A method for repairing multicast packets in a network carrying multicast packets in a multicast session from a source to a plurality of multicast recipients in that session, comprising:

15 receiving a subscriber request for multicast repair services;

monitoring received ones of the packets to said recipients with a repair server in the network in response to said subscriber request;

buffering portions of the packets during the session at a retransmit server in the network; and

20 detecting missing packets in said repair server and in response to said subscriber request, requesting missing packets from said retransmit server.

3. The method of claim 2, which further comprises:

25 allowing the recipient to selectively subscribe to the repaired multicast session as a network supplied service.

4. The method of claim 2, which further comprises:

limiting the recipient to receive the repaired multicast session as a network supplied service only if the recipient has subscribed to the multicast repair service.

30

5. The method of claim 2, which further comprises:

encrypting the repaired multicast session as a network supplied service and allowing the recipient access thereto only if the recipient has subscribed to the multicast repair service.

35

6. A method for repairing multicast packets in a network carrying multicast packets in a multicast session from a source to a plurality of multicast recipients in that session, comprising:

- receiving a request from a recipient's receiver to join a first IP multicast session;
- 5        intercepting said request and sending it to a controller in a repair server;
- forwarding the to a subscription server to determine if said recipient has  
subscribed to a repair service;
- receiving a positive response at the controller from the subscription server and  
determining whether a repair/encryption module exists in the repair server for the first  
10        multicast session;
- selecting at the controller a new IP multicast address and port number and a  
decryption key for a second IP multicast session;
- sending the new IP multicast address and port number and the decryption key to  
the translator/decryption module;
- 15        creating with the controller a new repair/encryption module and providing the  
new repair/encryption module with the new IP multicast address and port number and the  
encryption key;
- monitoring received ones of the packets to the recipient in the first session with  
the repair server;
- 20        buffering portions of the packets from the first session at a retransmit server in the  
network; and
- detecting missing packets in said repair server and in response to said subscriber  
request, requesting missing packets from said retransmit server.

- 25        7. A method of claim 6, which further comprises:  
         said monitoring including reading packets from said first IP multicast session and  
checking if there are any missing packets;
- requesting said retransmit server to obtain the missing packets;
- encrypting packets with the repair/encryption module and writing them to the  
30        second IP multicast session;
- processing the packets for the second IP multicast session by an IP stack on the  
receiver;
- sending the processed packets to the translator/decryption module;

decrypting the packets at the translator/decryption module and modifying the destination IP address and port number from values for the second session to values for the first session; and

sending the packets to the recipient;

5       whereby the recipient may request that a multicast session be repaired without interrupting any applications that already executing in the receiver.

8. The method of claim 7, which further comprises:

10       allowing the recipient to selectively subscribe to the repaired multicast session as a network supplied service.

9. The method of claim 7, which further comprises:

15       limiting the recipient to receive the repaired multicast session as a network supplied service only if the recipient has subscribed to the multicast repair service.

10. The method of claim 7, which further comprises:

20       encrypting the repaired multicast session as a network supplied service and allowing the recipient access thereto only if the recipient has subscribed to the multicast repair service.

11. A system for repairing multicast packets in a network including a source of multicast packets in a multicast session and a plurality of multicast recipients in that session, comprising:

25       a controller in a repair server for receiving and forwarding a request from a recipient to join a first IP multicast session;

      a subscription server receiving the request from the controller to determine if said recipient has subscribed to a repair service;

30       said controller receiving a positive response from the subscription server and determining whether a repair/encryption module exists in the repair server for the first multicast session;

      said controller generating a new IP multicast address and port number and a decryption key for a second IP multicast session;

      said controller sending the new IP multicast address and port number and the decryption key to the translator/decryption module;

35

a new repair/encryption module created by the controller, said controller providing thereto the new repair/encryption module with the new IP multicast address and port number and the encryption key;

5       said repair server monitoring received ones of the packets to the recipient in the first session;

          a retransmit server in the network buffering portions of the packets from the first session;

          said repair server detecting missing packets and in response to said subscriber request, requesting missing packets from said retransmit server.

10

12. The system of claim 11, which further comprises:

          said repair server reading packets from said first IP multicast session and checking if there are any missing packets and requesting said retransmit server to obtain the missing packets;

15       said repair/encryption module encrypting packets and writing them to the second IP multicast session;

          an IP stack in the receiver processing the packets for the second IP multicast session and sending the processed packets to the translator/decryption module;

20       said translator/decryption module decrypting the packets and modifying the destination IP address and port number from values for the second session to values for the first session and sending the packets to the recipient;

          whereby the recipient may request that a multicast session be repaired without interrupting any applications that already executing in the receiver.

## Abstract

A system and method provide for recipient-initiated automatic repair of IP multicast sessions. A multicast application on a receiver issues a request to join an IP multicast session "X". A translator/decryption module (TDM) on the receiver intercepts this request and sends it to a controller on a repair server. The controller sends a request to a subscription server to determine if this user has subscribed to the repair service. The controller receives a positive response from the subscription server and determines whether a repair/encryption module exists for this multicast session. If it does not, then the controller selects an IP multicast address, port number and decryption key for a new IP multicast session "Y". This information is returned to the TDM. The controller creates a repair/encryption module (REM) and provides the IP multicast address and port number for the new IP multicast session "Y" and an encryption key to the REM. Then, the TDM stores the session "Y" IP multicast address, port number and decryption key. The REM reads packets from IP multicast session "X" and checks if there are any missing packets. If there are missing packets, it requests one or more retransmit servers for session "X" to obtain the missing packets. The repair/encryption module encrypts the packets and writes them to IP multicast session "Y". The packets for IP multicast session "Y" are processed by the IP stack on the receiver, and are then sent to the translator/decryption module (TDM). The TDM decrypts these packets, modifies the destination IP address and port number from the values for session "Y" to those for session "X". The packets are then sent to the application. The application then presents the message contained in the packets to the subscriber of the IP multicast "X".

FIG. 1








FIG. 1A














FIG. 1E

FIG. 2A


PACKETS CURRENTLY BEING OUTPUT BY  
MULTICAST GROUP\_1 SOURCE 102



IP HEADER			UDP HEADER		RTP MESSAGE		
○○	SOURCE IP ADDRESS	DESTINATION IP ADDRESS	SOURCE PORT	DEST. PORT	SEQUENCE NUMBER	TIME STAMP	DATA
	RETRANS. SERVER 110A	MULTICAST GROUP_1 ADDRESS	CIRC. BUFFER 130A	DELAY BUFFER 140A			
				○○	285	090235	


PACKET 285

FIG. 2B



PACKETS CURRENTLY BEING DELIVERED TO DELAY BUFFER 140A


FIG. 2C



PACKETS CURRENTLY BEING DELIVERED TO ROUTER 122A  
WITH A 3-SECOND DELAY

FIG. 2D

RTCP SOURCE DESCRIPTION PACKET PERIODICALLY OUTPUT BY  
MULTICAST GROUP\_1 SOURCE 102



IP HEADER				UDP HEADER		RTCP SOURCE DESCRIPTION		
○○	SOURCE IP ADDRESS	DESTINATION IP ADDRESS	IP OPTIONS	SOURCE PORT	DEST. PORT	CNAME	TOOL	NOTE
	RETRANS. SERVER 110A	MULTICAST GROUP_1 ADDRESS		MSG. PROC. 132A	MSG. PROC. 142			
					○○			
							"VOICE TRACK IS 5 CHANNELS"	




+

+

FIG. 2E

RTCP SENDER REPORT PACKET PERIODICALLY OUTPUT BY  
MULTICAST GROUP\_1 SOURCE 102



IP HEADER				UDP HEADER		RTCP SENDER REPORT			
00	SOURCE IP ADDRESS	DESTINATION IP ADDRESS	IP OPTIONS	SOURCE PORT	DEST. PORT	SENDER'S ID	SENDER'S PACKET COUNT	SENDER'S OCTET COUNT	
	RETRANS. SERVER 110A	MULTICAST GROUP_1 ADDRESS		MSG. PROC. 132A	MSG. PROC. 142				
						GROUP_1 SOURCE 102	290	290,000	





FIG. 2F

REPAIRED MULTICAST SESSION 111'  
WHICH APPEARS TO RECIPIENT RECEIVERS 124A  
TO BE THE SAME MULTICAST GROUP\_1 SESSION  
FROM SOURCE 102




IP HEADER				UDP HEADER		RTP MESSAGE			
00	SOURCE IP ADDRESS	DESTINATION IP ADDRESS	IP OPTIONS		SOURCE PORT	DEST. PORT	SEQUENCE NUMBER	TIME STAMP	DATA
	REPAIR SERVER 120A	MULTICAST GROUP_1 ADDRESS			DELAY BUFFER 140A	RCVR 124			

PACKET 285



FIG. 2H

UNICAST REQUEST 150A  
TO FIRST RETRANSMIT SERVER 110A FOR MISSING PACKETS



IP HEADER			UDP SEGMENT		REQUEST SEGMENT
000	SOURCE IP ADDRESS REPAIR SERVER 120A	DESTINATION IP ADDRESS RETRANS. SERVER 110A	IP OPTIONS	SOURCE PORT MSG. PROC. 142A	DEST. PORT CIRC. BUFFER 130A
				000	DATA MISSING SEQUENCE NUMBERS 283 - 288

PACKET 150A →



FIG. 3A




FIG. 3B





FIG. 4A



+


+

# FIG. 4B

REPAIR SERVER

120A

MEMORY 402





IN THE UNITED STATES  
PATENT AND TRADEMARK OFFICE

**Declaration and Power of Attorney**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am an original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled **A Network-Based Service For Recipient-Initiated Automatic Repair Of IP Multicast Sessions**, the specification of which is attached hereto.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by an amendment, if any, specifically referred to in this oath or declaration.

I acknowledge the duty to disclose all information known to me which is material to patentability as defined in Title 37, Code of Federal Regulations, 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, 119 of any foreign application(s) for patent or inventors' certificate listed below and have also identified below any foreign application for patent or inventors' certificate having a filing date before that of the application on which priority is claimed:

**None**

I hereby claim the benefit under Title 35, United States Code, 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, 112, we acknowledge the duty to disclose all information known to us to be material to patentability as defined in Title 37, Code of Federal Regulations, 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

**None**

0933461 071399  
DECLARATION

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint the following attorney(s) with full power of substitution and revocation, to prosecute said application, to make alterations and amendments therein, to receive the patent, and to transact all business in the Patent and Trademark Office connected therewith:

Samuel H. Dworetsky	(Reg. No. 27873)
Thomas A. Restaino	(Reg. No. 33444)
Jose de la Rosa	(Reg. No. 34810)
Michele L. Conover	(Reg. No. 34962)
Robert B. Levy	(Reg. No. 28234)
Benjamin S. Lee	(Reg. No. 42787)
Alfred G. Steinmetz	(Reg. No. 22971)

I also appoint Christopher A. Hughes (Reg. No. 26914) and John E. Hoel (Reg. No. 26279) of Morgan & Finnegan as associate attorneys, with full power to prosecute said application, to make alterations and amendments therein, and to transact all business in the Patent and Trademark Office connected therewith.

Please address all correspondence to Mr. S. H. Dworetsky, AT&T Corp., P.O. Box 4110, Middletown, New Jersey 07748. Telephone calls should be made to Michele L. Conover at 908-903-6011.

Full name of 1<sup>st</sup> joint inventor: Vijay K. Bhagavath

Inventor's signature Vijay K Bhagavath Date 7/8/99

Residence: Lincroft, Monmouth County, New Jersey

Citizenship: India

Post Office Address: 45 Broadmoor Drive  
Lincroft, New Jersey 07738

65 E F 20 " T 94 E 550

Full name of 2<sup>nd</sup> joint inventor: Joseph Thomas O'Neil

Inventor's signature Joseph Thomas O'Neil Date 7/2/99

Residence: Staten Island, Richmond County, New York

Citizenship: United States of America

Post Office Address: 40 Hawley Avenue  
Staten Island, New York 10312

66E720" T.34E.3E.60

Full name of 3<sup>rd</sup> joint inventor: David Hilton Shur

Inventor's signature David Hilton Shur Date 7/12/99

Residence: <sup>Holmdel D.S.</sup> ~~Aberdeen~~, Monmouth County, New Jersey

Citizenship: United States of America

Post Office Address: ~~241 Perth Hill Court~~ <sup>D.S.</sup>  
~~Aberdeen, New Jersey~~ <sup>07747</sup>  
16 Beacon Court  
Holmdel  
NJ 07733

65555 "F" 945555

Post Office Address: 29 Crest Circle  
Matawan, New Jersey 07747

[illegible]